projectfire innovators in fire protection

Pump Initation Board

PIB-S-DS-03/21-1

SINGLE








Overview

The compact design, fast-fit initiation boards are designed for testing of pump initiation pressure switches for wet risers and automatic fire sprinkler systems. Each board incorporates a pressure switch for the jockey pump and a pressure switch for each duty pump. Each pressure switch can be isolated so its function and cut-in pressure can be verified during system servicing. Boards can be customised to include your company logo, contact details and a QR link for a how-to instruction video.

Specification

Board Material	4mm Aluminium Composite
Board Mounting	Unistrut
Pipework	.Galvanised Steel
Ball valves	. Lockable type
Gauges	Glycerine, no loss connectors
Non-return Valves	.Spring Loaded type
Gate Valves	Brass, with Control Orifice
Pressure-switches	Bailey & Mackey
Connections IN	Inlet Unions 1/2" (15 mm) BSP
Drain Connection OUT	1" (25mm)
Pressure rating	14 bar

Dimensions



Order		Pressure Switches		Dimensions			
	Model	Code	Fire-Pump	Jockey	Н	W	D
	2-Way	PIB-2WAY-S	1	1	690	510	180
	3-Way	PIB-3WAY-S	2	1	690	760	180
	4-Way	PIB-4WAY-S	3	1	690	1000	180
							m